

# AIRBLAST

*The Art of Powerful Cleaning...*



## EC-DECLARATION OF CONFORMITY

Hereby we declare that Airblast Paint Spray Hoses, are developed, manufactured, organised and approved according to international EN-ISO 9001 norms of the best possible materials.

| Art. no. | Description                  | Working pressure | Burst pressure |
|----------|------------------------------|------------------|----------------|
| 77000    | Paint Spray Hose 1/4" 1-wire | 400 bar          | 1300 bar       |
| 77050    | Paint Spray Hose 1/4" 2-wire | 483 bar          | 1930 bar       |
| 77100    | Paint Spray Hose 3/8" 1-wire | 300 bar          | 1000 bar       |
| 77150    | Paint Spray Hose 3/8" 2-wire | 450 bar          | 1380 bar       |

### General specifications:

Core : Nylon (PA)  
Pressure support : 1 or 2 Braids of Brass Coated High Tensile Steel Wire  
Cover : Polyurethane (PUR)  
Working temp. : -40° C to +95° C  
Colour : Blue

The Netherlands, 16 May 2008

A handwritten signature in black ink, appearing to be 'J.P.', with a horizontal line extending to the left from the bottom of the signature.

Airblast Quality Control

| Part no. | Rev. | Page   |
|----------|------|--------|
| DOC013   | A    | 1 of 1 |